

## HONEYMAN RENT-ALL

## **4423 SOUTH 84TH ST**



402-331-6013 / 1-800-260-6013



## **Bobcat Excavator / Backhoes**

Models	316 (5'1"Dig)	325 (8'-4"Dig)	329 (10'-2''Dig)
Swing	Conventional	Conventional	Conventional
Engine Make/ Model	Kubota / D722-EB	Kubota / D1703-M-E2B	Kubota / D1703-M-E2B
Horsepower (H.P.)	9.9 HP	27.7 HP	27.7 HP
Fuel Tank	2.4 Gal	14.1 Gal	12.3 Gal
Max Governed RPM	2000	2200	2200
Performance			
Operating Weight lbs	1676	6145	7098
Rated Lift Capacity			
(overblade@ground level)	497	1249	2038
Weight Class	0.76 t	2.7 t	n/a
Travel Speed - High/Low	1.2 / 1.2 mph	1.9 / 1.2 mph	1.9 / 1.2 mph
Arm Digging Force	1323 lbs	2820 lbs	3844 lbs
Bucket Digging Force	1874 lbs	4766 lbs	6866 lbs
Boom Swing - Left	87 deg	90 deg	90 deg
Boom Swing - Right	47 deg	50 deg	50 deg
Maximum Dig Depth	5'1" (61 in)	8'5" (100.6 in)	10'2" (122.1 in)
Max Dump Height	6'7" (79.1 in)	9' (109.41 in)	10'1" (121.6 in)
Maximum Reach	, ,	, , , , , , , , , , , , , , , , , , ,	, ,
at Ground Level	9' (108.5 in)	13' 7" (166.66 in)	16' (191.9 in)
Auxiliary Std Hydraulic Flow	5.4 GPM	12.3 GPM	14 GPM
Dimension			
Overall Length			
in Travel Position	9' 5" (114.7 in)	13' 7" (165.2 in)	16' (192.1 in)
Track / Machine Width	27.6 -35.4" in	4' 6" (55 in)	5'1" (60.63 in)
Cab Width	31.3"	4' 6" (55 in)	5'1" (60.63 in)
Height	7' 1" (84.8 in)	7' 8" (92.8 in)	7' 8" (92.8 in)
Description	The 316 ultra-compact	` ′	The Bobcat 329 excavator offers performance,
	excavator goes where	able to work in spaces where	comfort and reliability in a mid sized compact
		larger excavators would never	excavator. The 329's dual outlet, torque limiting
		fit. The 325 with its multi-	piston pump provides smooth, predictable control
	of 27.6 inches permits		for operators of all experience. The 329 provides
	entry to areas previously	everything from trenches to	easy to operate, "finger-tip" control of auxiliary
	inaccessible to compact		
	*	postholes, break up concrete	hydraulics, for precise control of attachment such
	excavators. Once access	and carve landscape features.	as the Hydraulic Clamp. The 329 is equipped with
	has been obtained, the	Its compact size and rubber	Bobcat's exclusive Engine and Hydraulic Monitor
	undercarriage can be	track flotation allow it to work	system, sensing vital machine functions to protect
	expanded to a width of	in muddy conditions and	your investment. The 1/4" exterior shell and
	35.6 inches for increased	overcome weight restrictions.	tailgate protect against damage to the machine,
	performance.		even in the most demanding applications.

Ask about other attachments for backhoes along with our loader/backhoe models (CASE 580 14'5" digging depth)